

ATV 1000CC MUD PRO - TECHNICAL SPECIFICATIONS

Adjustable Suspension

3500 LBS Winch

Comfortable Passenger
Seat with Backrest

5-inch TFT Display

Electric Power
Steering

Reliable Engine

Selectable 2WD-4WD

14" Bead Lock
Wheel Rims

Front LED
Headlights

Rear LED
Tail Lights

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	976 CC
Drive System Type	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok Front Differential
Engine Type	4-Stroke V-Twin, SOHC
Bore x Stroke	91 x 75 mm
MAX. Torque	95 N.m / 5500 RPM
MAX. Horsepower	92 HP / 7300 RPM
Starting System	Electric
Transmission	CVT Shaft
Fuel System	BOSCH Electronic Fuel Injection
Transmission/Final Drive	Automatic CVT P/R/N/L/H

DIMENSIONS & WEIGHT

Rack Capacity (F/R)	75 / 150 LBS
Estimated Dry Weight	1,014 lb (460 kg)
Fuel Capacity	4.8 Gallons
Ground Clearance	13 in. (33 cm)
Overall Vehicle Size (LxWxH)	2450 x 1290 x 1500 mm
Payload Capacity	740 lb (336 kg)
Person Capacity	2
Wheelbase	59 in. (1493 mm)
Seat Height	36.75 in. (93.3 cm)

BRAKES

Front / Rear Brakes	Dual 260 mm disc brakes with hydraulic twin-piston calipers
Parking Brake	Park In-Transmission and Hand Brake

ADDITIONAL SPECIFICATIONS

Front Suspension	Arched double A-arm with front sway bar
Rear Suspension	Torsional Trailing arm Independent (TTI)
Lighting	White LED Low/High & Red LED Tail / Brake Lights
Instrumentation	Digital Gauge, Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temp, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, DC Outlet

TIRES & WHEELS

Electronic Power Steering	Standard
Front Tires	28 x 9-14